THE PERSONAL ANALOG COMPUTER

Instruments for Instruction and Training

The concept of a Personal Analog Computer was proposed and specified at Case Institute of Technology by Professor James Reswick. Realizing that the use of analogue techniques greatly strengthened the students knowledge of physical systems, as well as their associated mathematics, he suggested the development of a "dormitory computer" specifically for student use. Each student would have his own portable unit, to use when and where he wanted to experiment. The use of the computer would require no special knowledge. The culmination of this proposal was the Personal Analog Computer.

What is the Personal Analog Computer

The Personal Analog Computer is an electronic demonstration system which utilizes individual miniature analog computer modules for visually representing and solving mathematical equations. Each of these modules performs one of the three basic mathematical operations, adding, multiplication by a constant, and integration.

By appropriately interconnecting these units and adjusting their parameters, a variety of complex physical systems may be simulated.

Behaviour of system variables can be monitored and plotted by the student.



Why was PAC Developed

The modular PAC (Personal Analog Computer) system was developed to provide students with a model intermediate between a dynamic physical system and the mathematical representation of that system.

After a student learns the physical features of a system, and the differential equations governing the system, he can interconnect PAC units to represent that system (or the equation). The Units will duplicate in real time the behaviour of the system variables.

PAC units provide the student with a personal experience associating physical behaviour with the solutions of a differential equation. They permit him to test his knowledge on a direct model personally at any time and in any place. This experimentation will reinforce both his physical and mathematical understanding.

Specifications

There are four PAC modules: ADDER, INTEGRATOR, COEFFICIENT MULTIPLIER, and the CONTROL UNIT.

Accuracy 1%

Panels Each module has a graphic panel face which indicates its mathematical operation. Panels are white and take crayon easily for marking purposes.

Interconnection Units are physically and electrically connected by four gold plated connectors. These carry power and control signals.

Variables Variables are interconnected by miniature banana patch cords.

Parameters Each unit has a front panel control to adjust its parameters.

Power Portable power is contained in the Control Unit.

Read Out Large center position precision meter, permits the measurement of any variable.

Figure 1; shows a typical physical system that a student might want to analyze, that of a spring and mass.

The parameters are the spring constant and the mass is assumed to be 1 for simplicity. The variables are x, displacement and f, force between the mass and the spring.



Figure 1

Figure 2; shows the differential equations that he would write showing the initial position of the mass displaced an amount X_0.

Figure 2

$$-KX = \frac{d^2x}{dt^2} \qquad \begin{matrix} t = 0 \\ x = X_0 \\ dx/dt = 0 \end{matrix}$$

DIFFERENTIAL EQUATION

Figure 3; shows the interconnection of PAC units. Each patch cord is a variable. Each box is a mathematical operation. The student sets the Coefficient Multiplier to the spring constant, the middle inegrator to X_0 as an initial condition, and the first Integrator to zero, meaning that the initial velocity is zero.

Pushing the SET switch on the Control Unit sets up this initial situation. Pushing the HOLD switch down starts the problem running and the X variables will follow the sine wave shown in the graph. Pushing the HOLD switch up causes the problem to run in ¼ second intervals.



Figure 3 PAC UNITS

Figure 4; whenever the student puts the HOLD switch in the neutral position, the problem is frozen and reading and plotting of variables can take place. This then is the resulting graphic solution.

Figure 4 GRAPHIC SOLUTION



The Integrator Unit, a typical PAC element

The integrator Unit is shown in Figure 6 without cover to indicate the packaging and precision components. Note particularly:

Precision Mylar condensor for integrating current
Two high-speed sealed reed relays for control
All printed-circuit transistorized construction
Large, high resolution potentiometer
Miniature transistorized operational amplifier

What does the PAC unit contain?

The PAC arithmetic units are highly engineered electronic circuits. Each unit contains an operational amplifier with an open loop gain of 1,000 and feedback components to perform the arithmetic operation. Every unit is pretested and calibrated to better than 1% accuracy.



The standard complement of PAC units consist of two Integrators, two Coefficient Multipliers, an Adder, and a Control Unit. Aside from the ordinary first and second order differential equations, PAC units are useful in demonstrating nonlinear differential equation solution, nonlinear circuits such as flipflops, multivibrators, waveform generators, and a number of interesting numerical experiments.

For further information or advice on applications, write or phone

PASTORIZA ELECTRONICS, INC.

285 Columbus Avenue Boston 16, Massachusetts

Telephone: COmmonwealth 6-1918

PASTORIZA
ELECTRONICS, INC.

PRICE LIST

6-99

THE PERSONAL ANALOG COMPUTER

Instruments for Instruction and Training

STANDARD SET

The most frequently used combination of PAC units permits solutions of the general second order differential equations. It consists of the following items:

1 Control Unit
1 Adder
2 Coefficient Multipliers
2 Integrators
1 Carrying Case

Assortment of Patch Cords,
Operating and Maintenance Instructions,
Application Literature, PAC Graph Paper

Price/Set	10 to 24	$350.00
	2 to 9	$370.00
	Single	$397.00

INDIVIDUAL UNIT	Single Unit	2 to 9	10 to 24
Control Unit	$122.00	$115.00	$105.00
Adder	54.00	51.00	48.00
Coefficient Multiplier	54.00	51.00	48.00
Integrator	63.00	59.00	57.00

ACCESSORIES

Six-inch Patch Cord	.90	.85	.80
Twenty-inch Patch Cord	1.15	1.05	.95
PAC Graph Paper (Pad)	1.00	.85	.75

Price: f.o.b. Newton
Terms: Net 30 Days

PASTORIZA ELECTRONICS, INC.
385 ELLIOT ST., NEWTON UPPER FALLS, MASSACHUSETTS 02164
617 • 332-2131

Modular
Analog-Digital and Digital-Analog Converters and Power Supplies

Modular Integrated Circuit

A-TO-D Converters



MODEL ADC-10IC provides 10 bit binary parallel output in 10 microsecond conversion time . . . accepts a ten volt input range . . . contains a Clock, Reference Supply, Resistor Network and Comparison Amplifier . . . triggered by an external command signal and provides a "Status" output level to indicate completion of the conversion.



MODEL ADC-12IC is a general purpose converter card which may be programmed to satisfy a wide range of specifications. For example, it will accept bipolar or unipolar input voltage ranges of varying amplitude and impedance requirements and will convert voltages into binary codes or various numbers of bits or into BCD code. This same basic card can therefore be supplied for a number of different system requirements without the usual expense and delays of "specials". MODEL ADC-12IC utilizes TTL micrologic and is available in extended temperature ranges (−55°C to +100°C) for military applications.

Miniature Precision Dual Power Supplies



MODEL MPD 15/100 is designed for use with operational amplifiers, instruments and systems. It provides ±15 VDC @ 100 Ma output from 110 VAC input, in a package only ¾" high including the power transformer. MPD 15/100 represents the first significant step in power supply miniaturization. The systems designer can now take full advantage of the comparable reductions in his circuits brought about by hybrid techniques.

Specifications include: 0.02% regulation (no load to full load), 0.005% regulation against line, complete short circuit protection and ambients from −25°C to +65°C. There are pin connectors for socket or printed circuit board mounting.

MODEL MPD 5/150 is a miniature card mounting power supply specifically designed for micrologic systems and instruments. It provides 5 volts at 600 Mas to power conventional DTL and TTL logic as well as 150 volts for neon or nixie readout lights.

This compact unit contains the entire power supply including power transformer, filtering, regulators and adequate heat dissipating surface. Input power is 5.5 watts, 105 to 125 VAC and 50 to 450 Hz.

Modular Integrated Circuit

D-TO-A Converters



D/A/D Series is a group of compatible integrated circuit modules for Digital-to-Analog and Analog-to-Digital Conversion Systems. MODEL RM—2734 is a Jam Transfer Storage Register for up to 12 bits. On strobe command it will accept and store numbers. MODEL RSN—2698 is a Switching Resistor Network and Reference Source. It can be switched by micrologic input levels and provides output binary weighted currents to a summing point. MODEL AM—2612 is a Combination of Two Operational Amplifiers with Feedback Networks for converting currents from RSN—2698 to output voltages. The use of operational amplifiers provides a variety of output ranges at low impedance.



MODEL DAC-10IC shown above is one of the many configurations in which the D/A/D Series Modules can be combined. It accepts 10 bit strobed parallel binary input in 1 microsecond slew time.

MODEL DAC-12IC accepts 6, 7, 8, 9, 10, 11 or 12 bit strobed parallel binary inputs.

PASTORIZA ELECTRONICS, INC.
385 ELLIOT ST., NEWTON UPPER FALLS, MASSACHUSETTS 02164
617 • 332-2131

SALES ENGINEERING REPRESENTATIVES



Area #1
R. H. STURDY CO. INC.
603 Worcester Road
Natick, Massachusetts 01760
(617) 235-2330

Area #2
J. D. RYERSON ASSOCIATES, INC.
P.O. Box 8369
Rochester, New York 14618
(716) 442-1900

1717 Harris Road
Penfield, N.Y.
(716) 377-2019

P.O. Box 1400
Syracuse, N.Y.
(315) 656-7419

Area #3
DONEGAN - ROSS COMPANY
120 West John Street
Hicksville, New York 11801
(516) 433-1940

P.O. Box 124
Chappaqua, New York 10514
(914) 238-8619

Area #4
CRANE & EGERT
107 West Ridge Pike
Conshohocken, Pa. 19428
(215) 277-0559

Area #5
TECHNITRON, INC.
23203 Lorain Road
North Olmsted, Ohio 44070
(216) 734-0960

1250 W. Dorothy Lane
Dayton, Ohio 45409
(513) 298-9964

14027 Puritan Avenue
Detroit, Michigan 48227
(313) 838-7324

114 Spring Grove Road
Pittsburgh, Pennsylvania 15235
(412) 371-1231

Area #6
GANS - FRYLING INC.
2030 Sixteenth Street
Arlington, Virginia 22201
(703) 527-3262

Area #7
BRENNAN ASSOCIATES
P.O. Box 907
211 Ewing Avenue
Clearwater, Florida 33517
(813) 446-5006

P.O. Box 8489
Ft. Lauderdale, Florida 33310

P.O. Box 1074
Huntsville, Florida 35800
(205) 852-5292

Area #8
GEORGE WEINREICH & ASSOCIATES
11554 E. Northwest Highway
Dallas, Texas 75218
(214) 321-2800

Area #9
W. K. GEIST COMPANY
1205 Airway P.O. Box 5004
Glendale, California 91201
(213) 245-9501

P.O. Box 746
Cupertino, California 95014
(408) 253-5433

7267 Bark Lane
San Jose, California

Area #10
KLEIN AEROSPACE
P.O. Box 1056
Englewood, Colorado 80110
(303) 781-4967

Area #11
CONSULT FACTORY

International
TERMINAL RADIO INTERNATIONAL LTD.
3 West 61st Street
New York, N.Y. 10023
(212) 246-2133

Canada
AHEARN & SOPER
844 Caledonia Road
Toronto 19, Canada
(416) 789-4325

PASTORIZA ELECTRONICS, INC.
385 ELLIOT ST., NEWTON UPPER FALLS, MASSACHUSETTS 02164
617 • 332-2131